



10mm triple wall or 16mm thick four wall - **Transparent** polycarbonate glazing.
10mm triple wall or 16mm thick four wall - **Opaline** polycarbonate glazing.

Specification

- Panel Depth / Width: **10mm** thick triple wall x 500mm wide.
16mm thick four wall x 500mm wide.
- System weight: **10mm** = 4.3kg/m². **16mm** = 5.9kg/m².
- Panel Colour: **Transparent** / **Opaline**.
- Sheet: Structured polycarbonate multi-cellular structure.
- Glazing Support Channels: Galvanised steel. Plastisol coated white or light grey.
- Clip system: polycarbonate UV protected clip profiles – colour to match glazing panels.
- Fastener location: two per each end & one in any intermediate purlins. Fix through channel with stainless steel screws and washers (type & size dependant on fixing structure).
- Gaskets: A number of seal gaskets are available to suit various details as required.
- Framing: various aluminium profiles are available to complement the system to provide framing and fit easily in nearly all situations.
- Durability: 10 year guarantee available.
- Light transmission: 73% for **Transparent** glazing and 63% for **Opaline** glazing.
- U value: **10mm** = 2.68 W/m²K. **16mm** = 2.04 W/m²k.
- Fire rating: Class 1 to BS476 Part 7 and Din 4102 B1.

canopiesuk

Chanters Way
Darwen
Lancashire
BB3 0GY

Tel: 01254 777 002
Fax: 01254 775 747
Email: karen@canopiesuk.co.uk
www.canopiesuk.co.uk

